

www.spitzenreiter.ru

(495) 988-95-96



Технические характеристики

Модель	Двигатель		Питание		Обороты R.P.M.	Цилиндры		Производи тельность л/мин	Давление Мпа	Ресивер Л	Размеры ДхШхВ (см)	Вес Кг.
	кВт	ЛС	В	Гц		Но. х Диам. мм	Ход мм					
QVB-0.17	1.5	2	220	50	980	2x51	46	170	0.8	6	75 x 60x 95	140
QVB-0.25	2.2	3	380	50	882	2x65	46	250	0.8	6	75 x 76 x 95	155
QWB-0.36	3	4	380	50	887	3x65	48	360	0.8	6	85 x 76 x 1 10	180
QVB-0.48	4	5.5	380	50	859	2x90	60	480	0.8	6	85 x 76 x 110	220
QWB-0.67	5.5	7.5	380	50	859	3x80	70	670	0.8	6	95 x 76 x117	255
QWB-0.90	7.5	10	380	50	859	3x90	70	900	0.8	6	95 x 76 x 117	295
QVB-0.15	1.5	2	220	50	890	1x65/1x51	46	150	1.25	6	75 x 76 x 95	140
QVB-0.20	2.2	3	380	50	882	1x65/1x51	46	200	1.25	6	75 x 76 x 95	155
QWB-0.30	3	4	380	50	887	2x65/1x51	48	300	1.25	6	85 x 76 x 1 10	180
QVB-0.40	4	5.5	380	50	859	1x90/1x65	60	400	1.25	6	85x 76 x 110	220
QWB-0.60	5.5	7.5	380	50	859	2x80/1x65	70	600	1.25	6	95 x 76 x 1 17	255
QWB-0.80	7.5	10	380	50	859	2x90/1x80	70	800	1.25	6	95x 76 x 117	290